

Pryco's STANDARD Day Tanks are available in either a U/L Listed (Label #142) or a basic (non-U/L Listed) design. In addition to the standard features listed below, U/L Listed tanks have additional internal reinforcement, an emergency vent properly sized to the tank, and a U/L Listed label (File #MH12807 - *Aboveground Tank for Flammable Liquids*).

Standard features include:

- * Removable 6½" Square Inspection Plate w/Gasket
- * Fuel Level Gauge
- * Heavy Duty Float Switch
- * "Press-to-Test" Switch
- * "Pump Running" Indicator Light
- * Four - 1" NPT Threaded Pipe Connections
- * One - 2" NPT Threaded Pipe Connection for Tank Vent
- * Tank Drain (Sized To Tank Capacity)
- * 1/3 hp thermally protected, 120vac, 1ph, 60hz, motor
- * 2 gpm bronze gear pump w/stainless steel shafts
- * Lift Lugs (on tanks 50 gallons and over)
- * Removable top cover
- * Epoxy coating inside
- * Pryco (medium) Gray exterior paint (or an industrial color of choice)

Pryco Tanks are fabricated of heavy gauge steel by certified welders. Each tank complies with NFPA 30 and is tested to 5 psi.

Shown to the right is a 25-gallon, U/L Listed, single-wall Standard Day Tank (PY25UL) with an optional #465 U/L Listed Enclosed Industrial Control Panel.



DOUBLE WALL TANKS

A totally enclosed outer shell may be added resulting in a double wall construction. Both the inner and the outer tanks are vented separately and are pressure tested at 5 psi.

When enclosing a U/L Listed day tank, an additional emergency vent is added to the outer tank the same size as the inner tank. (The U/L Listing is "*Secondary Containment Aboveground Tank for Flammable Liquids*", File MH12807.)

Day Tanks with a capacity of 25 gallons and more have all threaded connections located on the tank top (except the overflow, drains, and the double wall vent). The inner tank drain is piped through the outer shell.

RUPTURE BASINS

All Day Tanks can be set in a Rupture Basin (open top dike), including a tank with double wall construction. See Option 385 for sizes.

A Double Wall or a Rupture Basin may be equipped with an optional Leak Detector that will shut down the pump motor, turn on an alarm light and provide contacts for a remote signal — Options 295 and 395.

Weatherproof versions are also available.



STANDARD DAY TANKS
BASIC and U/L LISTED – SINGLE and DOUBLE WALL

SIZE IN US GAL.	SINGLE WALL			U/L LISTED SINGLE WALL			DOUBLE WALL			U/L LISTED DOUBLE WALL			R/B ⁽¹⁾
	MODEL	WEIGHT		MODEL	WEIGHT	VENT	MODEL	WEIGHT		MODEL	WEIGHT	VENT	WEIGHT
5	PY5	88		PY5UL	92	2	PY5DW	165		PY5ULDW	170	2	102
10	PY10	94		PY10UL	98	2	PY10DW	182		PY10ULDW	187	2	111
15	PY15	109		PY15UL	113	2	PY15DW	215		PY15ULDW	220	2	119
25	PY25	122		PY25UL	126	2	PY25DW	243		PY25ULDW	248	2	139
50	PY50	192		PY50UL	166	2	PY50DW	335		PY50ULDW	340	2	183
60	PY60	185		PY60UL	192	3	PY60DW	385		PY60ULDW	394	3	201
75	PY75	200		PY75UL	207	3	PY75DW	416		PY75ULDW	425	3	219
100	PY100	220		PY100UL	227	3	PY100DW	465		PY100ULDW	474	3	259
150	PY150	266		PY150UL	273	3	PY150DW	599		PY150ULDW	608	3	324
200	PY200	385		PY200UL	396	4	PY200DW	904		PY200ULDW	918	4	433
275	PY275	453		PY275UL	464	4	PY275DW	1104		PY275ULDW	1118	4	528
300	PY300	463		PY300UL	469	4	PY300DW	1117		PY300ULDW	1131	4	556
400	PY400	532		PY400UL	543	4	PY400DW	1279		PY400ULDW	1293	4	623
500	PY500	573		PY500UL	584	4	PY500DW	1391		PY500ULDW	1405	4	742
600	PY600	613		PY600UL	624	4	PY600DW	1484		PY600ULDW	1498	4	838
700	PY700	660		PY700UL	671	4	PY700DW	1619		PY700ULDW	1633	4	913
800	PY800	703		PY800UL	714	4	PY800DW	1810		PY800ULDW	1824	4	991
900	PY900	747		PY900UL	771	6	PY900DW	1925		PY900ULDW	1958	6	1071
1000	PY1000	789		PY1000UL	804	6	PY1000DW	2003		PY1000ULDW	2036	6	1152

NOTE#1 - Add R/B (Rupture Basin) Weight to Tank Weight to determine total weight.